



FXLQ-P

The floor standing unit can be installed quickly and easily in new or existing facilities

The floor standing unit can be installed quickly and easily in new or existing facilities in a variety of applications.

The Daikin VRV indoor unit range is one of the widest on the market, offering no less than 26 stylish and elegant models in 116 different variants – all designed to maximise comfort, minimise operating noise and simplify installation and servicing.

Designed to fit rooms of any size and shape, Daikin indoor units are also user friendly, ultra reliable, easy to control and quiet in operation.

All indoors units comply with the Ecodesign legislation by adopting DC fans in all indoor units, improving their energy efficiency.

Features and benefits:

- > Stylish modern casing finished in pure white (RAL9010) and iron grey (RAL7011)
- > Its low height enables the unit to fit perfectly beneath a window
- > Requires very little installation space
- > Wired remote control can easily be integrated in the unit using customised slot
- > Unit can be installed as free standing model by use of optional back plate
- > Wall mounted installation facilitates cleaning beneath the unit where dust tends to accumulate



FXLQ20-25



BRC1E52A/B



BRC7C62

FXLQ-P

Indoor unit				FXLQ20P	FXLQ25P	FXLQ32P	FXLQ40P	FXLQ50P	FXLQ63P
Cooling capacity	Nom.		kW	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Nom.		kW	2.5	3.2	4.0	5.0	6.3	8.0
Power input - 50Hz	Cooling	Nom.	kW	0.049		0.090		0.110	
	Heating	Nom.	kW	0.049		0.090		0.110	
Casing Colour				Fresh white (RAL9010) / Dark grey (RAL7011)					
Dimensions	Unit	H x W x D	mm	600x1,000x232		600x1,140x232		600x1,420x232	
Weight	Unit			27	32		38		
Fan-Air flow rate - 50Hz	Cooling	High/Low	m ³ /min	7/6		8/6	11/8.5	14/11	16/12
Sound power level	Cooling	Nom.	dB(A)	-					
Sound pressure level	Cooling	High/Low	dB(A)	35/32		38/33		39/34	40/35
Refrigerant	Type				R-410A				
Piping connections	Liquid/OD/Gas/OD/Drain	mm		6.35/12.7/O.D. 21					9.52/15.9/O.D. 21
Power supply	Phase/Frequency/Voltage	Hz/V		1~/50/ 220-240					
Current - 50Hz	Maximum fuse amps (MFA)	A		15					

Options & accessories

Adapters and controls	FXLQ 20~63P
BRC1E52A/B Premium wired remote control with full text interface and back light	•
BRC1D52 Standard wired remote control with weekly timer	•*4
Infrared remote control including receiver	BRC4C65
BRC2E52A Simplified wired remote control for heat recovery	•
BRC3E52A Simplified wired remote control for heat pump	•
DCS302C51 Central remote control	•
DCS301B51 Unified ON/OFF control	•
DST301B51 Schedule timer	•
DCM601A51 Intelligent Touch Manager	•
External wired temperature sensor	KRCS01-1
External wireless temperature sensor	K.RSS
Wiring adapter for external monitoring/control via dry contacts and setpoint control via 0-140 Ω	KRP4A51
Wiring adapter for external central monitoring / control (controls 1 entire system)	KRP2A51
Wiring adapter with 4 output signals (compressor / Error, Fan, Aux. heater, Humidifier output)	KRP1B61
Wiring adapter with 2 output signals (compressor / Error, Fan)	-
Adapter for multi-tenant (24VAC PCB power interface)	EKMTAC
External control adapter for outdoor unit	-
Installation box / Mounting plate for adapter PCBs (For units where there is no space in the switchboard)	-
Connector for forced-off contact	standard
Connection to centralised control	standard
Electrical box with earth terminal (2 blocks)	-
Electrical box with earth terminal (3 blocks)	-

Other options	FXLQ 20~25P	FXLQ 32~40P	FXLQ 50~63P
Decoration panel (obligatory for cassette units, optional for others, rear panel for FXLQ)	EKRDP25A	EKRDP40A	EKRDP63A
Kit for mounting of decoration panel direct onto unit	-	-	-
Panel spacer for reducing required installation height	-	-	-
Sealing kit for 3-directional or 2 directional air discharge	-	-	-
Decoration panel for air discharge	-	-	-
Fresh air intake kit	-	-	-
Air discharge adapter for round duct	-	-	-
Replacement long life filter	-	-	-
Drain pump kit	-	-	-
Sensor kit	-	-	-
Noise filter (for electromagnetic use only)	-	-	-
L-type piping kit (for upward direction)	-	-	-

*4 Not recommended because of the limitation of the functions

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.

