



Fully flat cassette

600sq 4-way blow - VRV indoor unit

FXZQ-A

Fitting within the ceiling tiles and fully flat with the ceiling itself

Unique in the market, the fully flat cassette is a remarkable blend of iconic design and engineering excellence, with an elegant matt crystal white or a silver and matt crystal white finish. Fitting flush within the ceiling modules and fully flat with the ceiling itself, the cassette is both stylish and unobtrusive.

Features and benefits:

- > Unique design in the market: integrates fully flat into the ceiling and fits flush within an individual ceiling tile
- > Remarkable blend of iconic design and engineering excellence with an elegant finish in white or a combination of silver and white
- > 15 class unit especially developed for small or well-insulated rooms, such as, small offices
- > The presence sensor (optional) adjusts the set point with standard 1°C if no one is detected in the room, it is possible to adjust the set point with 2, 3 or 4°C (optional). It also automatically directs air flow away from any person to avoid draught
- > The floor sensor (optional) detects the average floor temperature and ensures even temperature distribution between ceiling and floor, reducing cold feet problems
- > Individual louvre control: one louvre can be easily closed via the wired remote control (BRC1E52A) in case you would refurbish or rearrange your interior
- > Low energy consumption thanks to specially developed small tube heat exchanger, DC fan motor and drain pump
- > Fresh air intake for healthy living
- > Standard drain pump with 850mm lift



FXZQ-A
(silver and Matt Crystal white panel)





FXZQ-A
(Matt Crystal white panel)



BRC1E52A/B



BRC7F530W/S*



FXZQ-A

Indoor unit			FXZQ15A	FXZQ20A	FXZQ25A	FXZQ32A	FXZQ40A	FXZQ50A	
Cooling capacity	Nom.	kW	1.7	2.2	2.8	3.6	4.5	5.6	
Heating capacity	Nom.	kW	1.9	2.5	3.2	4.0	5.0	6.3	
Power input - 50Hz	Cooling	Nom.	0.043			0.045	0.059	0.092	
	Heating	Nom.	0.036			0.038	0.053	0.086	
Dimensions	Unit	H x W x D	mm						
Weight	Unit	kg	15.5			16.5		18.5	
	Model	Fully Flat in white BYFQ60CW (standard panel)							
Decoration panel	Colour	White (N9.5)							
	Dimensions	H x W x D	mm						
	Weight	kg	2.8						
	Model	Fully flat in white with silver BYFQ60CS							
Decoration panel 2	Colour	White (N9.5) + Silver							
	Dimensions	H x W x D	mm						
	Weight	kg	2.8						
	Model	Old style panel BYFQ60B3							
Decoration panel 3	Colour	White (RAL9010)							
	Dimensions	H x W x D	mm						
	Weight	kg	2.7						
	Model	Old style panel BYFQ60B3							
Fan-Air flow rate - 50Hz	Cooling	High/Nom./Low	m ³ /min	8.5/7/6.5	8.7/7.5/6.5	9/8/6.5	10/8.5/7	11.5/9.5/8	14.5/12.5/10
	Heating	High/Nom./Low	m ³ /min	8.5/7/6.5	8.7/7.5/6.5	9/8/6.5	10/8.5/7	11.5/9.5/8	14.5/12.5/10
Sound power level	Cooling	High/Nom.	dB(A)	49/-		50/-	51/-	54/-	60/-
Sound pressure level	Cooling	High/Nom./Low	dB(A)	31.5/28/25.5	32/29.5/25.5	33/30/25.5	33.5/30/26	37/32/28	43/40/33
	Heating	High/Nom./Low	dB(A)	31.5/28/25.5	32/29.5/25.5	33/30/25.5	33.5/30/26	37/32/28	43/40/33
Refrigerant	Type	R-410A							
Piping connections	Liquid/OD/Gas/OD/Drain	mm	6.35/12.7/VP20 (I.D. 20/O.D. 26)						
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240						
Current - 50Hz	Maximum fuse amps (MFA)	A	16						

(1) Dimensions include control box

Options & accessories

Adapters and controls	FXZQ 15~50A
BRC1E52A/B Premium wired remote control with full text interface and back light	•
BRC1D52 Standard wired remote control with weekly timer	•*4
Infrared remote control including receiver	BRC7F530W (white) *9 *10 BRC7F530S (grey) *9 *10 BRC7EB530 (standard) *9 *10
BRC2E52A Simplified wired remote control for heat recovery	-
BRC3E52A Simplified wired remote control for heat pump	-
DCS302C51 Central remote control	•
DCS301B51 Unified ON/OFF control	•
DST301B51 Schedule timer	•
DCM601A51 Intelligent Touch Manager	•
External wired temperature sensor	KRCS01-4
External wireless temperature sensor	K.RSS
Adaptor for wiring (interlock for fresh air intake fan)	-
Wiring adapter for external monitoring/control via dry contacts and setpoint control via 0-140 Ω	KRP4A53 *2
Wiring adapter for external central monitoring / control (controls 1 entire system)	KRP4A52
Wiring adapter with 4 output signals (compressor / Error, Fan, Aux. heater, Humidifier output)	EKRP1B2
Wiring adapter with 2 output signals (compressor / Error, Fan)	KRP1B57
Adapter for multi-tenant (24VAC PCB power interface)	DTA114A61
External control adapter for outdoor unit	-
Installation box / Mounting plate for adapter PCBs (For units where there is no space in the switchboard)	KRP1A101
Connector for forced-off contact	-
Connection to centralised control	-
Electrical box with earth terminal (2 blocks)	-
Electrical box with earth terminal (3 blocks)	-
Electrical box with earth terminal	-
Digital input adapter	-

Other options	FXZQ 15~50A
Decoration panel	BYFQ60CW (white) BYFQ60CS (grey) BYFQ60B3 (standard)
Kit for mounting of decoration panel direct onto unit	-
Panel spacer for reducing required installation height	KDDQ44B60 (standard)
Sealing kit for 3-directional or 2 directional air discharge	BDBHQ44C60 (white & grey)
Fresh air intake kit	KDDQ44XA60
Air discharge adapter for round duct	-
Filter chamber for bottom suction	-
Replacement long life filter	KAFQ441BA60
Drain pump kit	standard
Sensor kit	BRYQ60AW 9(white) BRYQ60AS (grey)
Noise filter (for electromagnetic use only)	-

*2 Installation box is necessary for these adapters

*4 Not recommended because of the limitation of the functions

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.

